



Type: Model: With lid: round bucket 11-0100 BIS6 P-01Bis/5; P-01Bis/6; P-01Bis/5F;

PHOTO OF PRODUCT

DIMENSIONS/WEIGHT


Upper diameter (inside): 122,4 mm (b)
Upper diameter (with flange): 132 mm (a)
Upper diameter (with handles): 135 mm
Bottom diameter (external): 105,4 mm (c)

Height (with standard lid): 131,0 mm (h) Height (with lid for foiling): 134,5 mm

Nominal capacity: 1 000 ml Total capacity: 1 285 ml Total usable capacity: 1 200 ml

Container weight with handle: 37 g
Handle weight (strap): Handle weight (PP): Handle weight (metal): -


Weight tolerance: +/- 5%
Dimension tolerance: +/- 1 mm





DECORATION

	Dry offset (up to 6 colors)	IML
Width (B):	=	356,9 mm
Height (H):	5.	112,9 mm



LIDS

Name: P-01Bis/5
Foiling: No
Weight: 9 g
IML: Yes
Offset: No



Name: P-01Bis/6 Foiling: No Weight: 9 g IML: Yes Offset: No



Name: P-01Bis/5F Foiling: Yes Weight: 10 g IML: Yes Offset: No



RAW MATERIAL / TRANSPORT AND WAREHOUSING

- Buckets and lids are made of polypropylene (PP)
- Warehousing: In the case of stacking pallets with filled containers put weight uniformly, using for example proper separators.
- Filling and closing conditions: max. content temperature during filling 95°C, during stacking content temperature should be lower than 45°C. Put not more than 2 warm containers in the stack.

When temperature decrease to 25-30° containers are characterized by optimal rigidity and mechanical parameters allowing stacking for maximal static load as below.

Load on the lower container:

- Transportation of filled containers: containers may be stacked to the 66% of maximal static load.
- Palletizing of containers: product with density 1,1 g/cm3 according to the customer practice giving consideration to the mentioned earlier values.
- All materials and dyes used to produce container or lid designed for the food sector are approved for food contact.
- This guarantee is valid 12 months from date of delivery. During this time, the package should be used. All packages from a single pallet should be used immediately after unpacking.
- Manufacturer is not responsible for container deformation because of stacking of single pallets or putting on them an extra load.





/ Verified 22.06.2020 /



SVP Négoce, ZAC du Clos Neuf, 16 rue Denis Papin, 14840 DEMOUVILLE Tél: 02 31 26 16 64

E-mail: contact@svpnegoce.com

NÉGOCE RCS de Caen: 822 624 805 TVA intracommunautaire: FR 39 822 624 805

N° de SIRET: 822 624 805 00039 Code APE: 4690Z